

# Gammes de débits standards

## Pour M310 et M325



M310 (M10) $\Delta p$ : 0 - 500 mbar			
Dim.		Corps	Gammes de débits en l/min
Taraudé	DN15 1/2"	G15 (GL15)	0,2 - 2
			0,5 - 5
			1 - 10
			2,5 - 25
			5 - 50
Taraudé	DN20 3/4"	G20 (GL20)	1 - 10
			2,5 - 25
			5 - 50
			8 - 80
Taraudé	DN25 1"	G25 (GL25)	1 - 10
			2,5 - 25
			5 - 50
			12 - 120
Taraudé	DN40 1 1/2"	GL40	5 - 50
			10 - 100
			30 - 300
Entre brides	DN15 1/2"	FA15 F15SS	0,2 - 2
			0,5 - 5
			1 - 10
			5 - 50
Entre brides	DN20 3/4"	FA20 F20SS	1 - 10
			5 - 50
			8 - 80
Entre brides	DN25 1"	FA25 F25SS	1 - 10
			5 - 50
			17,5 - 175*
Entre brides	DN32 1 1/4"	FA32 F32SS	5 - 50
			10 - 100
			30 - 300**
Entre brides	DN40 1 1/2"	FA40 F40SS	5 - 50
			10 - 100
			30 - 300
Entre brides	DN50 2"	FA50 F50SS	10 - 100
			25 - 250
			50 - 500
Entre brides	DN65 2 1/2"	FA65 F65SS	25 - 250
			50 - 500
			80 - 800***
Entre brides	DN80 3"	FA80 F80SS	25 - 250
			50 - 500
			100 - 1000
Entre brides	DN100 4"	FA100 F100SS	50 - 500
			100 - 1000
			200 - 2000
Entre brides	DN125 5"	FA125 F125SS	100 - 1000
			200 - 2000
			300 - 3000
Entre brides	DN150 6"	FA150 F150SS	100 - 1000
			200 - 2000
			400 - 4000
Entre brides	DN200 8"	FA200 F200SS	200 - 2000
			500 - 5000
			700 - 7000
Entre brides	DN250 10"	FA250 F250SS	200 - 2000
			500 - 5000
			1200 - 12000

M325 (M25) $\Delta p$ : 0 - 1250 mbar			
Dim.		Corps	Gammes de débits en l/min
Taraudé	DN15 1/2"	G15 (GL15)	0,5 - 5
			1 - 10
			2,5 - 25
			5 - 50
			7,5 - 75
			12 - 120
Taraudé	DN20 3/4"	G20 (GL20)	1 - 10
			2,5 - 25
			5 - 50
			12 - 120
Taraudé	DN25 1"	G25 (GL25)	5 - 50
			10 - 100
			20 - 200
Taraudé	DN40 1 1/2"	GL40	10 - 100
			20 - 200
			40 - 400
Entre brides	DN15 1/2"	FA15 F15SS	0,5 - 5
			1 - 10
			5 - 50
			7,5 - 75
Entre brides	DN20 3/4"	FA20 F20SS	1 - 10
			5 - 50
			12 - 120
Entre brides	DN25 1"	FA25 F25SS	5 - 50
			10 - 100
			25 - 250*
Entre brides	DN32 1 1/4"	FA32 F32SS	10 - 100
			20 - 200
			40 - 400**
Entre brides	DN40 1 1/2"	FA40 F40SS	10 - 100
			25 - 250
			50 - 500
Entre brides	DN50 2"	FA50 F50SS	20 - 200
			50 - 500
			80 - 800
Entre brides	DN65 2 1/2"	FA65 F65SS	30 - 300
			60 - 600
			120 - 1200***
Entre brides	DN80 3"	FA80 F80SS	50 - 500
			100 - 1000
			200 - 2000
Entre brides	DN100 4"	FA100 F100SS	50 - 500
			100 - 1000
			300 - 3000
Entre brides	DN125 5"	FA125 F125SS	100 - 1000
			300 - 3000
			500 - 5000
Entre brides	DN150 6"	FA150 F150SS	100 - 1000
			300 - 3000
			700 - 7000
Entre brides	DN200 8"	FA200 F200SS	200 - 2000
			500 - 5000
			110 - 11000
Entre brides	DN250 10"	FA250 F250SS	200 - 2000
			500 - 5000
			1700 - 17000

\*Pour ANSI: Max.: 0-120 \*\*Pour ANSI: Max.: 0-200  
\*\*\*Pour ANSI: Max.: 0-700

\*Pour ANSI: Max.: 0-120 \*\*Pour ANSI: Max.: 0-200  
\*\*\*Pour ANSI: Max.: 0-700

- Gammes de débits liquides
- Les gammes de pressions différentielle ( $\Delta p$ ) peuvent être modifiées sur site grâce au logiciel M-Win